

## FEATURES

### TP-VBA (Without boiler)

Vacuum, up-steaming and blowing ironing table + iron, with electrically heated board and suction.  
 Work table dimensions 1.200 x 400 x 250mm.  
 Blowing unit needs external supply of compressed air.  
 Adjustable temperature of the board by means of a thermostat.  
 Built-in single phase suction unit.  
 Works by means of a pedal.  
 Electric heated board.  
 Needs to be connected to an external steam supply.  
 Voltage: 230V I +N 50Hz.

### TPC-VBA (With boiler)

Vacuum up-steaming and blowing ironing table + iron with suction and electrically heated board, controlled by a thermostat.  
 Work table dimensions 1.200 x 400 x 250mm.  
 Blowing unit needs external supply of compressed air.  
 Built-in electric steam boiler. Iron included. Second iron as option.  
 Automatic water feeding, automatic pressure control.  
 Feeding pump and emptying valve.  
 Works by means of a pedal.  
 Electrical heating.  
 Voltage: 400V III +N / 230V III.



## OPTIONS

- Sleeve arm TP-VBA and TPC-VBA
- Steam gun TP-VBA and TPC-VBA
- Sliding trolley with light TP-A, TPC-A, TP-VBA and TPC-VBA
- Second iron (only models with boiler - TPC)

CAPACITY	UNIT.	TPC-VBA
		CON CALDERA
Boiler	-	YES
Boiler capacity	L	7
Board dimensions	mm	1.200 x 400 x 250
Adjustable height of board	-	NO
<b>OPTIONS</b>		
Swinging arm with heated sleeve shape	-	OPT
Steam gun	-	OPT
Sliding trolley with balancer and lighting	-	OPT
Second steam iron assembly	-	OPT
<b>POWER</b>		
Vacuum motor	kW	0,45
Pump motor	kW	0,75
Iron heater	kW	0,83
Board heater	kW	-
Boiler heater	kW	6-7,5
Sleeve-arm heater (option)	kW	0,09
<b>CONNECTIONS</b>		
Ø Water inlet	BSP	3/8"
Ø Boiler exhaust (with boiler)	BSP	3/8"
Ø Steam inlet	BSP	-
Steam pressure	BAR	4,5
Steam Consumption	kg/h	-
Ø Air inlet	BSP	1/4"
Air pressure	BAR	4-8
Air Consumption	NI/min	5
<b>DIMENSIONS / PACKING DIMENSIONS</b>		
Net width / Gross width	mm	1.680 / 1.880
Net depth / Gross depth	mm	580 / 680
Net height / Gross height	mm	920 / 1.270
Net weight / Gross weight	kg/h	141 / 165
Volume	m <sup>3</sup>	0,90 / 1,62
<b>OTHER</b>		
Voltage 50-60Hz	V/Hz	230/400V III 50
Sound level	dB	75