



### TOUCH II

- **TOUCH II:** Easy-to-use microprocessor, fully programmable with 7" touchscreen.
- Multilingual interface.
- Dual-side screen.
- Detergent dosing: 8 standard signals + 6 optional.
- USB port: configure, update and analyse without internet.
- Programme customisation based on your needs.



### OUTSTANDING FEATURES

- 3 water inlets.
- WET CLEANING.
- Skinplate cabinet with stainless steel top - easy to clean.
- Heating model: electric and steam.
- Automatic drum positioning (optional) + UPS system for short power cuts.



### EFFICIENCY

- WATER SAVING: three configurable saving levels.
- OPTIMAL LOADING: manual load weight input.
- Ready for **ECOTANK XL** connection.
- High G Factor: lower residual moisture > shorter drying time.
- Low water consumption.
- Automatic weighing system (option).
- **LEMS pulse concentrator by Onnera** (ask us about this new option).



### CONNECTIVITY

- **DOMUSCONNECT:** standard, free IoT connectivity.
- Remote technical service.
- Machine monitoring.
- Remote business management.



### ERGONOMICS

- Large-diameter door - ideal for loading and unloading.
- Drum opens easily with push-button.
- Ergonomic height for easier loading.
- Loading height: door base 960 mm.



### MAINTENANCE

Electric components on the left side, mechanical components on the right side and connections on the top (protected from water and detergents).

Technical menu: statistics, alarms, autotest, data recovery for technicians and maintenance.



### OTHERS

2 opposed doors. Pass-through barrier washer.  
Ready to be connected to dosing pumps.  
Grey skinplate outer casing.  
Drum and vat in stainless steel AISI 304.  
Frequency inverter to control imbalance.  
CE approved product



### OPTIONS

- License IoT - DOMUSCONNECT
- Ready for ECOTANK XL conn. 1" for barriers ASA-100
- Weighing sensor system on feet for ASA-100. Includes kit with 6 extra dosing signals.
- 6 extra dosing signals card for automatic liquid dosing
- Double heating Electric + Steam
- Titration valve
- End of cycle light alarm
- 4 compartment detergent box
- Stainless steel outer casing
- Stainless steel frame
- Screen and panels protector
- Maritime wooden packing for
- 230V 3~ 50/60Hz
- 440V 3~ 60Hz (marine)

DRUM	UNIT.	ASA-100 TOUCH II	
Load capacity 1:9	Kg	100	
	lb	220,5	
Load capacity 1:10	Kg	90	
	lb	198,4	
Volume	l	900	
	ft³	31,78	
Diameter	mm	1.050	
	inch	41,3	
Depth	mm	1.032	
	inch	40,6	
Drum compartments	Nº	2	
GENERAL DETAILS			
Washing speed	rpm	45	
Spining speed	rpm	750	
G Factor	-	325	
TOUCH II Control	-	7"	
Double screen	-	STD	
Motor break	-	STD	
Double drainage	-	STD	
DOOR			
Drum opening dimensions	mm	900 x 500	
	inch	35,4 x 19,6	
Vat opening dimensions	mm	960 x 700	
	inch	37,8 x 27,55	
Height door bottom	mm	960	
	inch	37,8	
POWER			
Motor	kW	15	
Electric heating (elec. mod)	kW	60	
Total electric power (elec. mod)	kW	75	
kW	15		
Total electric power (steam mod)	kW	15	
CONNECTIONS			
Tension 230V I + N + T 50/60Hz	Nº x mm²/A	-	-
Tension 230V III + T 50/60Hz	Nº x mm²/A	4 x 50 / 200A	4 x 10 / 40A
Tension 400V III + N + T 50/60Hz	Nº x mm²/A	5 x 25 / 120A	5 x 6 / 25A
Water inlets number	-	3	
Water inlet	mm	26/34	
	inch	1"	
Water pressure	bar	3 - 5	
	psi	43 - 72	
Steam inlet (steam mod)	inch	3/4"	
Steam pressure	bar	4-8	
	psi	58-116	
Drain number	-	2	
Drain evacuationc capacity	l/min	2x200	
	cfm	2x5,65	
Drain	mm	80	
	inch	3"	
OVERALL DIMENSIONS			
Net / Gross width	mm	1.742 (1.894)** / 1.890	
	inch	68,6 (74,6)** / 74,4	
Net / Gross depth	mm	1.468 / 1.540	
	inch	57,8 / 60,6	
Net / Gross height	mm	1.982 / 2.150	
	inch	78 / 84,6	

Net / Gross weight	kg	1.900 / 1.958
	lb	4.189 / 4.316,7
Volume	m <sup>3</sup>	6,26
	ft <sup>3</sup>	221

\* Program No 2, 100 % load  
 \*\* Measurement with the detergent option added

1. Electrical connexion  
 2. Cold water inlet  
 3. Soft water inlet  
 4. Hot water inlet  
 5. Liquid products inlet  
 6. Main switch  
 7. Control panel  
 8. Emergency stop  
 9. Door opening  
 10. USB port  
 11. Dosing pumps connexion  
 12. Steam inlet  
 13. Exhaust  
 14. Cold water for detergent box  
 15. Compressed air connection  
 16. Manual rotation  
 17. Compressed air steam valve  
 18. Ethernet port

	A	B	C	A1	B1	C1	D	E	F	G	H	I	J	K	L	O	P	Q	R	S	T	U	V	W	X	Y
ASA-100	1.742	1.468	1.982	1.677	1.346	1.954	921	82	162	262	382	183	172	1.013	1.279	83	1.163	1.737	1.765	1.777	150	192	122	502	1.179	183