



ELECTRONIC PROGRAMMER

M programmer: push buttons to control temperature and time.



OUTSTANDING FEATURES

Reversing drum action as standard.
Stainless steel drum as standard.
Frequency inverter as standard.



EFFICIENCY

DOUBLE FLOW - mixed axial-radial airflow.
Big fluff filter.



VERSATILITY

Make to order - Customisation
OPL > Self-service - Standard OPL model easily trasformable to coin laundry uses.



ERGONOMICS

Drawer as fluff filter, stainless steel mesh.
Biggest door diameters.



MAINTENANCE

Hinged control panel: easy and ergonomic access.
Technical menu: statistics for technicians and maintenance with external console (with console option).



OTHERS

Grey skinplate outer casing, stainless steel look.
SOFT DRY - new drum with stamped holes.
COOL DOWN - anti-wrinkle at the end of the cycle.
Heating options: electric or gas except DTM2-22 XP only gas.
CE approved



OPTIONS

- Double doorglass (order 1 unit per column)
- Screen in M programmer (2 units)
- Fluff filter with grid 0,3 mm (standard in STACK is 0,6 mm)
- Stainless steel front and side panels DTM2-14 XP
- Maritime wooden packing DTM2-14 XP
- Front panel in stainless steel DTM2-11/14/18 XP
- 400V 3~ 50 Hz 11/14/18/22 XP
- 400V 3N 60 Hz 11/14/18/22 XP
- 230V 3~ 60 Hz 11/14/18/22 G XP
- 230V 3~ 60 Hz 11/14/18 E XP
- 440/480V 3~ 60 Hz 11/14/18/22 XP (marine)
- Several payment systems for self-service

CAPACITY & DRUM	UNIT.	DTM2-14 XP	
Capacity 1/18	Kg	15,0 x 2	
	lb	33,1 x 2	
Capacity 1/20	Kg	13,5 x 2	
	lb	29,8 x 2	
Ø Drum	mm	750	
	inch	29,5	
Drum length	mm	610	
	inch	24	
Drum volume	l	270	
	cu ft	9,53	
Ø Door hole	mm	574	
	inch	22,6	
Door center height	mm	547 / 1522	
	inch	21,54 / 59,92	
Height from floor to bottom of door	mm	189 / 1164	
	inch	7,32 / 45,83	
ELECTRIC HEATING			
Evaporation capacity	L/h *	14,5 x 2	
	US gallon/h *	3,83 x 2	
Hourly output	Kg/h **	29 x 2	
	lb/h **	64 x 2	
Installed heating power	kW	18 x 2	
Installed electrical power	kW	37,34	
Drum motor power	kW	0,37 x 2	
GAS HEATING			
Evaporation capacity (gas model)	L/h	15,7 x 2	
	US gallon/h	4,14 x 2	
Hourly output (gas model)	Kg/h	31,4 x 2	
	lb/h	69,2 x 2	
Installed gas heating power	kcal/h ***	17627 x 2	
	Btu/h ***	69996 x 2	
	kW ***	20,5 x 2	
Installed electrical power	kW	1,34	
Consumption of propane gas average (G31)	Kg/h	0,82 x 2	
	lb/h	1,82 x 2	
Instant natural gas consumption (G20)	m³/h	2,17 x 2	
	cfm	1,28 x 2	
Ø Gas inlet	BSPP ISO 228-1	3/4"	
VENTILATION			
Fan motor power	kW	0,25 x 2	
Nominal air flow rate	m³/h	500 x 2	
	cfm	294,28 x 2	
Ø Fume exhaust	mm	200	
	inch	7,87	
HEAT EMISSION			
Maximum total heat emission 10-8% (9-7%)	kW	3,3	
	Btu/h	11198	
Max. front heat emission 7-5% (4-2%)	kW	1,2	
	Btu/h	4199	
CONNECTIONS		E	G / S
Tension 230V - I + N + T	Nº x mm² / A	-	3 x 2,5 / 16 (5*)
Tension 230V - III + T	Nº x mm² / A	4 x 50 / 125	3 x 2,5 / 16 (5*)
Tension 400V - III + N + T	Nº x mm² / A	5 x 16 / 63	3 x 2,5 / 16 (6*)
NET DIMENSIONS / D. WITH PACKING			
Net / gross width	mm	785 / 865	
	inch	30,9 / 34,1	

Net / gross depth	mm	1135 / 1218
	inch	44,7 / 48
Net / gross height	mm	1994 / 2126
	inch	78 / 83,7
Net / gross weight	Kg	299 / 312
	lb	659 / 688
OTHERS		
Max. sound level (at 1m in front)	dB	64


* Drying conditions: full load (1/20) of towels, drying temperature 90°C.

** Kg dry linen per hour. Drying conditions: full load (1/20) of towels, drying temperature 90°C.

*** Calculation of thermal power from PCI.

(5*) Connect 2 phases and earth.

(6*) Connect phase, neutral and earth.



- 01. Power supply
- 02 Fumes output Ø200
- 03 2 Sprinkler valves 3/4"
- 04 Gas inlet 3/4"
- 05 Ethernet connection (only touch control)
- 06 ON/OFF control rocker switch

		A	B	C	D	E	F	G	H	I	J	K	L	M	N1	N2	O	P	Q
DTM2-14 XP	mm	1980	1447	259	1234	131	785	1135	735	83	318	575	77	113	97	197	73	54	1163