

 **FEATURES****MP-A (without boiler)**

Vacuum ironing table + iron, electrically heated.

- Working table: 1,200 x 400 x 250 mm
- Plate temperature adjustable by thermostat
- Built-in single-phase vacuum unit
- Foot pedal operation
- Requires external steam supply and return
- Voltage: 230V 1+N 50Hz

MP-A-C (with boiler)

Vacuum ironing table + iron, electrically heated.

- Working table: 1,200 x 400 x 250 mm
- Electric boiler with iron included
- Thermostat-controlled
- Automatic water feeding and pressure control
- Feed pump and drain valve
- Foot pedal operation
- Voltage: 400V 3+N / 230V 3 / 230V 1+N 50Hz
- **MP-A-C PLUS:** height-adjustable plate from 750 to 950 mm

**OPTIONS**

- Vacuum sleeve arm for MP-A/MPA-C/MP-AS/MP-AS-C/MP-AC PLUS
- Steam gun for MP-A/MPA-C/MP-AS/MP-AS-C/MP-AC PLUS
- Sliding trolley with light for MP-A/MPA-C/MP-AS/MP-AS-C/MP-AC PLUS
- Second iron (models with electric boiler only)

CAPACITY	UNIT.	MP-A-C
		CON CALDERA
Boiler	-	YES
Boiler capacity	L	5
Board dimensions	mm	1.200 x 400 x 250
Adjustable height of board	-	NO
OPTIONS		
Swinging arm with heated sleeve shape	-	OPT
Steam gun	-	OPT
Sliding trolley with balancer and lighting	-	OPT
Second steam iron assembly	-	OPT
POWER		
Vacuum motor	kW	0,45
Pump motor	kW	-
Iron heater	kW	0,83
Board heater	kW	1
Boiler heater	kW	3,9
Sleeve-arm heater (option)	kW	0,09
CONNECTIONS		
Ø Water inlet	BSP	3/8"
Ø Boiler exhaust (with boiler)	BSP	3/8"
Ø Steam inlet	BSP	-
Steam pressure	BAR	2,8
Steam Consumption	kg/h	-
Ø Air inlet	BSP	-
Air pressure	BAR	-
Air Consumption	NI/min	-
DIMENSIONS / PACKING DIMENSIONS		
Net width / Gross width	mm	1.550 / 1.520
Net depth / Gross depth	mm	580 / 580
Net height / Gross height	mm	950 / 1.140
Net weight / Gross weight	kg/h	87 / 103
Volume	m ³	0,85 / 1,01
OTHER		
Voltage 50-60Hz	V/Hz	230/400 V 3 50
Sound level	dB	68