

TOUCH II

User friendly and totally programmable microprocessor with 7" touch screen.
USB Connection.
Online platform free of charge for programming, telemetry, data analysis...thanks to the IoT.
Videos shown on display: ads, instructions (useful for coin laundry).
37 languages.

OUTSTANDING FEATURES

Reversing drum action as standard.
Stainless steel drum as standard.
Frequency inverter as standard.

EFFICIENCY

EFFICIENT DRY - Intelligent humidity control, with new drum inlet temperature control.
AIR RE-CYCLE - Efficient air recirculation system.
THERMAL INSULATION - Complete air-flow circuit and double door glass.
FULL FLOW - Optimized system with mixed airflow.
Big fluff filter.

VERSATILITY

Make to order - customisation.
Wet Cleaning.

CONNECTIVITY

Standard IoT **DOMUSCONNECT**.
Management for laundries: OPL and self-service.

ERGONOMICS

Drawer as fluff filter, stainless steel mesh.
Biggest door diameters.
Opening sense of door adjustable on site.

MAINTENANCE

Hinged control panel: easy and ergonomic access.
Technical menu: statistics for technicians.

OTHERS

Grey skinplate outer casing, stainless steel look.
NEW: Geared motor drive on models DTT-45 to DTT-80
SFEX - Integrated Fire Extinguishing System.
SOFT DRY - new drum with stamped holes.
COOL DOWN - anti-wrinkle at the end of the cycle.
Heating options: electric, gas and steam.
CE approved




OPTIONS

- License IoT - DOMUSCONNECT
- Back panel with air filter DTT-11 to DTT-35
- Natural gas heated tumble dryer
- Opposite door opening DTT-11 to DTT-35
- Tropicalized model
- Dosing spraying of perfume
- Fluff filter with grid 0,6mm (standard is 0,3mm)
- Fluff filter with grid 1,2mm (standard is 0,3mm)
- Stainless steel front and side panels DTT-22
- Front panel in stainless steel DTT-22
- Steam battery in stainless steel DTT-22
- Low pressure steam battery DTT-22
- Maritime wooden packing DTT-22
- 400V III 60Hz DTT-11 to DTT-35
- 230V III 50Hz DTT-22/28/35 E
- 230V III 60Hz DTT-22/28/35 E
- 230V III 60Hz DTT-11 to DTT-35 G/S
- 440/480V III 60Hz DTT-22/28/35 (maritime)

CAPACITY & DRUM	UNIT.	DTT-22 ECO-ENERGY
Capacity 1/18	Kg	24,4
	lb	53,9
Capacity 1/20	Kg	22
	lb	48,5
Ø Drum	mm	835
	inch	32,87
Drum length	mm	800
	inch	31,5
Drum volume	l	440
	cu ft	15,54
Ø Door hole	mm	574
	inch	22,60
Door center height	mm	1.030
	inch	40,55
Height from floor to bottom of door	mm	672
	inch	26,46
ELECTRIC HEATING		
Evaporation capacity	L/h	20
	US gallon/h	5,3
Hourly output	Kg/h	40
	lb/h	88,2
Installed heating power	kW	24
Installed electrical power	kW	25,17
Drum motor power	kW	0,37
GAS HEATING		
Evaporation capacity (gas model)	L/h	22,30
	US gallon/h	5,891
Hourly output (gas model)	Kg/h	44,60
	lb/h	98,3
Installed gas heating power	kcal/h	26655
	Btu/h	105775,6
Installed gas heating power	kW	31
Installed electrical power	kW	1,17
Instant propane gas consumption (G31)	Kg/h	2,66
	lb/h	5,86
Instant natural gas consumption (G20)	m ³ /h	3,28
	cfm	1,93
Ø Gas inlet	BSPP ISO 228-1	1/2"
STEAM HEATING		
Installed steam heating power	kW	49,20
	Btu/h	167877
Installed electrical power	kW	1,17
Steam consumption (8 barG) - Standard	kg/h	87
Steam consumption (116 psiG)	lb/h	104,8
Steam pressure	barG	6 - 9
	psiG	87 - 130,5
Standard steam inlet - outlet	BSPT- ISO7.1	1"
Standard steam inlet - outlet	NPT ANSI B1.20.1 Tapered	1"
Steam pressure (low pressure)	barG	3 - 6
	psiG	43,5 - 94
Low pressure steam inlet - outlet	BSPT- ISO7.1	1"
THERMAL OIL HEATING		
Installed heating power	kW	-
Installed electrical power	kW	-
Fluid consumption (T max 175°C)	m ³ /h	-
Thermal oil connection	BSP	-

VENTILATION			
Fan motor power	kW	0,75	
Nominal air flow rate	m ³ /h	1.500	
	cfm	882,87	
Ø Fume exhaust	mm	200	
	inch	7,87	
HEAT EMISSION			
Maximum total heat emission	kW	1,92	
	Btu/h	6555,1	
Max. front heat emission	kW	1,2	
	Btu/h	4097	
CONNECTIONS			
Tension 230V - I + N + T	Nº x mm ² / A	E	G / S
Tension 230V - III + T	Nº x mm ² / A	4 x 25 / 80A	3 x 1,5 / 16A
Tension 400V - III + N + T	Nº x mm ² / A	5 x 10 / 40A	3 x 1,5 / 16A
NET DIMENSIONS / D. WITH PACKING			
Net / gross width	mm	890 / 970	
	inch	35,04 / 38,19	
Net / gross depth	mm	1.255 / 1.345	
	inch	49,41 / 52,95	
Net height / gross height	mm	1.812 / 1.940	
	inch	71,34 / 76,38	
Net / gross weight	Kg	210 / 230	
	lb	462,97 / 507,06	
OTHERS			
Sound level	dB	65	



- 01 Power supply
- 02 Fumes output Ø 200
- 03 Gas inlet 1/2"
- 04 Steam inlet 3/4"
- (DTT-11-14-18)
- 04 Steam inlet 1" (DTT-22)
- 05 Condensate outlet 3/4"
- (DTT-11-14-18)
- 05 Condensate 1" (DTT-22)
- 06 Sprinkler valve 3/4"
- 07 Ethernet connection (only TOUCH Control)

	A	B	C	D	D1	E	E1	F	G	H	I	J	K	L	M	N	O	P	Q	R
DTT-18 ECO-ENERGY	1.694	1.447	689	1.354	1.422	68	68	785	1.125	735	380	870	575	1.226	133	180	830	65	35	805
DTT-22 ECO-ENERGY	1.812	1.552	743	1.430	1.532	112	55	890	1.255	735	107	920	575	1.344	238	180	885	65	37	860