

FEATURES

- In a space of just 18 m², it dries and irons, folds and stacks linen.
 - Folding types: longitudinal and crosswise.
 - Can be operated by a single operator.
 - Maximum output up to 290 kg/h.*
 - Adjustable ironing speed up to 18 m/min.*
 - Maximum temperature: 165°C.
 - Automatic ironing speed control.
 - Automatic cooling of the ironing roller.
 - Available in one or two work lanes.
 - Intuitive and programmable 7" touchscreen. Optional mobile arm.
 - Fume extraction system with automatic fan cleaning.
 - Stackers can be added (optional).
 - Customisable with different accessories.
- Featured options:

SALIDA LATERAL / Side exit



1 Apilador lat. compacto por palas
Side standard stacker by blades



2 Apilador lat. Roll-Off (por arrastre)
Side stacker Roll-Off

SALIDA POSTERIOR / Rear exit



3 Recogedor post. + bypass (2/4 vías)
Rear collector + bypass (2/4 lanes)



SMARTY
Plegadora prend. pequeñas
Small garment folder

*Maximum production and speed, variable depending on model, configuration and working conditions.



OPTIONS

- Compact side stacker by blades
- Roll-off side stacker
- Vacuum belts to help linen feeding
- Automatic 1 lane clamp feeder (needs option of vacuum feeding belts)
- By pass for rear exit
- Rear exit with 800mm table (it includes bypass)
- Four folding lanes (lengthfolds only)
- High motorised table, side exit (no stacker) H=805 mm
- Low table, side exit (no stacker) H=480 mm
- Rotating arm for the control panel
- 2 lanes rear collector small garments (it needs bypass option)
- 4 lanes rear collector small garments (it needs bypass option)
- Double air pressure for thick linen
- Linen rejection system (dirty or torn)
- Remote service (SPE, SP, S)
- Maritime packaging SPE
- Maritime packing for compact side stacker by blades
- Maritime packing for Roll-off side stacker 1
- Maritime packing for small pieces collector 2 lanes
- Maritime packing for small pieces collector 4 lanes
- Different voltage from 400V 3~ +N 50 Hz

GENERAL DATA	UNIT.	SPE600-2-3300
Theoretical production* elec/steam/atm. Gas heating	Kg/h	110-140
Theoretical production* radiant gas burner	Kg/h	132-168
Ø Roll	mm	600
Working width	mm	3.300
Height floor-feeding	mm	1.050
Working speed	m/min	3-12
Control type	-	Digital
No. of programs	Nº.	20
FOLDING		
Drying	-	YES
Ironing	-	YES
Longitudinal folding	-	YES
Cross folding	-	YES
Lateral stacking (Roll-Off or compact stacker)	-	OPT
FOLDING		
1 lane - lengthfold	Nº.	1-2
1 lane - crossfold	Nº	1-2-3
2 lanes - lengthfold	Nº	1-2
2 lanes - crossfold	Nº	1-2
POWER		
Electric model - Consumption	A	78
Electric model - Heating power	kW	54
Electric model - Total electrical power	kW	57,1
Steam model - Consumption	Kg/h	125
Steam model - Power (max 12 bar)	kW	75
Steam model - Total electrical power	kW	3,1
Liquefied gas (LPG) model - Consumption	m³/h	3,2
Liquefied gas (LPG) model - Power	kW	86,3
Natural gas (NG) model - Consumption	m³/h	8,5
Natural gas (NG) model - Power	kW	80,3
Gas LPG / NG model - Total electrical power	kW	3,1
CONNECTIONS		
Ø Gas inlet	BSP	1"
Ø Steam inlet (12 bar max.)	BSP	1"
Ø Condensed (steam models)	BSP	1/2"
Ø Air inlet	mm	12
DIMENSIONS		
Net width / gross width	mm	4.440 / 4.600
Net depth / gross depth	mm	2.210 / 2.280
Net height / gross height	mm	2.040 / 1.970
Net weight / gross weight	Kg	3.080 / 3.680
Volume	m³	20,02 / 20,66
OTHERS		
Exhaust outlet	Nº	2
Exhaust outlet Ø	mm	120
Air extraction flow rate	m³/h	2 x 630
Air consumption (6.5 bar)	NI/h	15.000
Noise level	dB	<80

* 50% residual moisture, 140gr/m² of cotton, 100% roll use