

FEATURES

TP-VBA (Without boiler)

Vacuum, up-steaming and blowing ironing table + iron, with electrically heated board and suction.
 Work table dimensions 1.200 x 400 x 250mm.
 Blowing unit needs external supply of compressed air.
 Adjustable temperature of the board by means of a thermostat.
 Built-in single phase suction unit.
 Works by means of a pedal.
 Electric heated board.
 Needs to be connected to an external steam supply.
 Voltage: 230V I +N 50Hz.

TPC-VBA (With boiler)

Vacuum up-steaming and blowing ironing table + iron with suction and electrically heated board, controlled by a thermostat.
 Work table dimensions 1.200 x 400 x 250mm.
 Blowing unit needs external supply of compressed air.
 Built-in electric steam boiler. Iron included. Second iron as option.
 Automatic water feeding, automatic pressure control.
 Feeding pump and emptying valve.
 Works by means of a pedal.
 Electrical heating.
 Voltage: 400V III +N / 230V III.



OPTIONS

- Sleeve arm TP-VBA and TPC-VBA
- Steam gun TP-VBA and TPC-VBA
- Sliding trolley with light TP-A, TPC-A, TP-VBA and TPC-VBA

CAPACITY	UNIT.	TP-VBA
		SIN CALDERA
Boiler	-	NO
Boiler capacity	L	-
Board dimensions	mm	1.200 x 400 x 250
Adjustable height of board	-	NO
OPTIONS		
Swinging arm with heated sleeve shape	-	OPT
Steam gun	-	OPT
Sliding trolley with balancer and lighting	-	OPT
Second steam iron assembly	-	NO
POWER		
Vacuum motor	kW	0,45
Pump motor	kW	-
Iron heater	kW	0,83
Board heater	kW	-
Boiler heater	kW	-
Sleeve-arm heater (option)	kW	0,09
CONNECTIONS		
Ø Water inlet	BSP	-
Ø Boiler exhaust (with boiler)	BSP	3/8"
Ø Steam inlet	BSP	-
Steam pressure	BAR	4-5
Steam Consumption	kg/h	10-15
Ø Air inlet	BSP	1/4"
Air pressure	BAR	4-8
Air Consumption	NI/min	5
DIMENSIONS / PACKING DIMENSIONS		
Net width / Gross width	mm	1.680 / 1.880
Net depth / Gross depth	mm	580 / 680
Net height / Gross height	mm	920 / 1.270
Net weight / Gross weight	kg/h	141 / 165
Volume	m ³	0,90 / 1,62
OTHER		
Voltage 50-60Hz	V/Hz	230V 50
Sound level	dB	75