

FEATURES

MP-ASV

Vacuum, steaming and blowing ironing table + iron, electrically heated.

- Working table: 1,200 x 400 x 250 mm
- Blowing system requires external compressed air supply (compressor)
- Air connection: 1/4", pressure: 5 bar
- Plate temperature adjustable by thermostat
- Built-in single-phase vacuum unit
- Foot pedal operation
- Requires external steam supply and return
- Height adjustable from 750 to 950 mm
- Voltage: 230V 1+N 50Hz

MP-ASV-C (with boiler)

Vacuum, steaming and blowing ironing table + iron, electrically heated.

- Working table: 1,200 x 400 x 250 mm
- Blowing system requires external compressed air supply (compressor)
- Air connection: 1/4", pressure: 5 bar
- Electric boiler with iron included (second iron optional)
- Thermostat-controlled
- Automatic water feeding and pressure control
- Feed pump and drain valve
- Foot pedal operation
- Voltage: 400V 3+N / 230V 3



OPTIONS

- Vacuum sleeve arm for MP-ASV/MP-ASV-C
- Steam gun for MP-ASV/MP-ASV-C
- Sliding trolley with light for MP-A/MPA-C/MP-AS/MP-AS-C/MP-AC PLUS

CAPACITY	UNIT.	MP-ASV
		SIN CALDERA
Boiler	-	NO
Boiler capacity	L	-
Board dimensions	mm	1.200 x 400 x 250
Adjustable height of board	-	NO
OPTIONS		
Swinging arm with heated sleeve shape	-	OPT
Steam gun	-	OPT
Sliding trolley with balancer and lighting	-	OPT
Second steam iron assembly	-	NO
POWER		
Vacuum motor	kW	0,45
Pump motor	kW	-
Iron heater	kW	0,83
Board heater	kW	-
Boiler heater	kW	-
Sleeve-arm heater (option)	kW	0,09
CONNECTIONS		
Ø Water inlet	BSP	-
Ø Boiler exhaust (with boiler)	BSP	3/8"
Ø Steam inlet	BSP	-
Steam pressure	BAR	4-5
Steam Consumption	kg/h	10-15
Ø Air inlet	BSP	1/4"
Air pressure	BAR	4-8
Air Consumption	NI/min	5
DIMENSIONS / PACKING DIMENSIONS		
Net width / Gross width	mm	1.680 / 1.880
Net depth / Gross depth	mm	580 / 680
Net height / Gross height	mm	920 / 1.270
Net weight / Gross weight	kg/h	141 / 165
Volume	m ³	0,90 / 1,62
OTHER		
Voltage 50-60Hz	V/Hz	230V 1 50
Sound level	dB	75