

FEATURES

TP-BA (Without boiler)

Vacuum and blowing ironing table + iron, with electrically heated board and suction.

Work table dimensions 1.200 x 400 x 270mm.

Blowing unit needs external supply of compressed air.

Adjustable temperature of the board by means of a thermostat.

Built-in single phase suction unit.

Works by means of a pedal.

Electric heated board.

Needs to be connected to an external steam supply.

Voltage: 230V I +N 50Hz.

TPC-BA (With boiler)

Vacuum and blowing ironing table + iron with suction and electrically heated board and suction.

Work table dimensions 1.200 x 400 x 270mm.

Blowing unit needs external supply of compressed air.

Adjustable temperature of the board by means of a thermostat.

Built-in electric steam boiler. Iron included. Second iron as option.

Automatic water feeding, automatic pressure control.

Feeding pump and emptying valve.

Works by means of a pedal.

Electrical heating.

Voltage: 400V III +N / 230V III or 230V I +N 50Hz.



OPTIONS

- Sleeve arm for TP-A, TPC-A, TP-BA and TPC-BA
- Steam gun for TP-A, TPC-A, TP-BA and TPC-BA
- Sliding trolley with light TP-BA and TPC-BA
- Second iron (only models with boiler - TPC)

CAPACITY	UNIT.	TPC-BA
		CON CALDERA
Boiler	-	YES
Boiler capacity	L	5
Board dimensions	mm	1.200 x 400 x 270
Adjustable height of board	-	YES
OPTIONS		
Swinging arm with heated sleeve shape	-	OPT
Steam gun	-	OPT
Sliding trolley with balancer and lighting	-	OPT
Second steam iron assembly	-	OPT
POWER		
Vacuum motor	kW	0,45
Pump motor	kW	-
Iron heater	kW	0,83
Board heater	kW	1
Boiler heater	kW	3,9
Sleeve-arm heater (option)	kW	0,09
CONNECTIONS		
Ø Water inlet	BSP	3/8"
Ø Boiler exhaust (with boiler)	BSP	3/8"
Ø Steam inlet	BSP	-
Steam pressure	BAR	2,8
Steam Consumption	kg/h	-
Ø Air inlet	BSP	-
Air pressure	BAR	-
Air Consumption	NI/min	-
DIMENSIONS / PACKING DIMENSIONS		
Net width / Gross width	mm	1.500 / 1.520
Net depth / Gross depth	mm	600 / 580
Net height / Gross height	mm	1.800 / 1.120
Net weight / Gross weight	kg/h	100 / 116
Volume	m³	1,62 / 0,99
OTHER		
Voltage 50-60Hz	V/Hz	230/400V III 50
Sound level	dB	70