DOMUS

WINNING THE FUTURE THROUGH INNOVATION

MP-AS-C
Vacuum and blowing ironing tables

FEATURES

MP-AS (without boiler)

Vacuum and blowing ironing table + iron, electrically heated.
- Working table: 1,200 x 400 x 270 mm
- Blowing system requires external compressed air supply (compressor)
- Air connection: 1/4", pressure: 5 bar
- Plate temperature adjustable by thermostat
- Built-in single-phase vacuum unit
- Foot pedal operation
- Requires external steam supply and return
- Height adjustable from 750 to 950 mm
- Voltage: 230V 1+N 50Hz

MP-AS-C (with boiler)

Vacuum and blowing ironing table + iron, electrically heated.
- Working table: 1,200 x 400 x 270 mm
- Blowing system requires external compressed air supply (compressor)
- Air connection: 1/4", pressure: 5 bar
- Electric boiler with iron included
- Thermostat-controlled
- Automatic water feeding and pressure control
- Feed pump and drain valve
- Foot pedal operation



OPTIONS

- Vacuum sleeve arm for MP-A/MPA-C/MP-AS/MP-AS-C/MP-AC PLUS
- Steam gun for MP-A/MPA-C/MP-AS/MP-AS-C/MP-AC PLUS
- Sliding trolley with light for MP-ASV/MP-ASV-C
- Second iron (models with electric boiler only)

CAPACITY	UNIT.	MP-AS-C
		CON CALDERA
Boiler	-	YES
Boiler capacity	L	5
Board dimensions	mm	1.200 x 400 x 270
Adjustable height of board	-	YES
OPTIONS		
Swinging arm with heated sleeve shape	-	OPT
Steam gun	-	OPT
Sliding trolley with balancer and lighting	-	OPT
Second steam iron assembly	-	OPT
POWER		
Vacuum motor	kW	0,45
Pump motor	kW	-
Iron heater	kW	0,83
Board heater	kW	1
Boiler heater	kW	3,9
Sleeve-arm heater (option)	kW	0,09
CONNECTIONS		
Ø Water inlet	BSP	3/8"
Ø Boiler exhaust (with boiler)	BSP	3/8"
Ø Steam inlet	BSP	-
Steam pressure	BAR	2,8
Steam Consumption	kg/h	-
Ø Air inlet	BSP	-
Air pressure	BAR	-
Air Consumption	Nl/min	-
DIMENSIONS / PACKING DIMENSIONS		
Net width / Gross width	mm	1.500 / 1.520
Net depth / Gross depth	mm	600 / 580
Net height / Gross height	mm	1.800 / 1.120
Net weight / Gross weight	kg/h	100 / 116
Volume	m^3	1,62 / 0,99
OTHER		
Voltage 50-60Hz	V/Hz	230/400V 3 50
Sound level	dB	70