

## FEATURES

Flatwork ironer with roll sizes: 2.600 and 3.300mm long and diameter 600, 800 and 1.000mm.

Panels in painted steel.

One or two working lanes: one lane for bedsheets and two lanes for tablecloth and smaller pieces.

Lengthfold (1 or 2 folds) and crossfold (up to 3 folds).

Folding system by photocells and compressed air.

Two types of linen stacker, with possibility to program the number of items stacked. The stacker can be positioned on either side of the machine.

Frequency control.

Feeding and ironing belts are NOMEX.

Touch-screen control: programs can be created with speed control (between 3 and 18mts/min), temperature and folding parameters.

Automatic stop after cooling down (at 80°C).

Big output capacity, depending on the residual moisture of the linen, up to 290kg/hour directly from the high spin washer extractor.

Electric, gas or steam heating.

Efficient gas models with radiant burner (increase of 25% more production, available in diameter 800 models and standard in diameter 1.000 models).

Powerful exhaust system.




## OPTIONS

- Stacker - it can stack up to 15 tablecloth, 10 bedsheets
- Compact (roll-off) stacker - it can stack up to 5 tablecloth
- Vacuum feeding belts to help the linen feeding
- Automatic 1 lane clamp feeder without vacuum feeding belts
- By pass for rear exit
- Rear exit with table + bypass
- Small pieces back collector: 2 lanes + bypass included
- Small pieces back collector: 4 lanes + bypass included
- Double air pressure in length folds for thicker linen
- Linen reject system (dirty or torn)
- Remote service
- Different voltage from 400V III +N 50 Hz
- Maintenance Kit for Ironers
- Maritime packing for SPE
- Maritime packing for side stacker
- Maritime packing for ROLL OFF
- Maritime packing for small pieces collector 2 lanes
- Maritime packing for small pieces collector 4 lanes




GENERAL DATA		UNIT.	SPE1000-2-2600
Theoretical production* elec/steam/atm. Gas heating		Kg/h	225
Theoretical production* radiant gas burner		Kg/h	257
Ø Roll		mm	1.000
Working width		mm	2.600
Height floor-feeding		mm	1.050
Working speed		mt/min	4-18
Control type		-	Digital
No. of programs		Nº.	20
Side stacker		Nº.	OPT.
FOLDING			
1 lane - lengthfold		Nº.	1-2
1 lane - crossfold		Nº	1-2-3
2 lanes - lengthfold		Nº	1-2
2 lanes - crossfold		Nº	1-2
POWER			
Electric heating		kW	90
Max. electric power electric heating		kW	93,4
Gas heating (natural / LPG)		kW	120,90
Max. electric power gas heating		kW	3,9
Steam heating		kW	120
Max. electric power steam heating		kW	3,9
CONNECTIONS			
Ø Gas inlet		BSP	1"
Ø Steam inlet (12 bar max.)		BSP	1-1/4"
Ø Condensed (steam models)		BSP	1"
Ø Air inlet		BSP	12
DIMENSIONS / PACKAGING DIMENSIONS			
Net width / gross width		mm	3.740 / 3.900
Net depth / gross depth		mm	2.290 / 2.300
Net height / gross height		mm	2.480 / 2.290
Net weight / gross weight		Kg	3.960 / 4.410
Volume		m³	21,24 / 20,54
OTHERS			
No. Fume outlet		Nº	2
Ø Fume outlet		mm	160
Extraction rate		m³/h	2 x 1.000
Compressed air consumption (6,5 bar)		mm	21.000
Sound Level		dB	70

\* 50% residual moisture, 140gr/m² of cotton, 100% roll use

Compact Stacker  
(roll-off)



Stacker



Compact Stacker

	L	P
<b>SPE1000-2600</b>	4.425	2.385
<b>SPE1000-3300</b>	5.125	2.385

Stacker

	L	P
<b>SPE1000-2600</b>	5.105	2.476
<b>SPE1000-3300</b>	5.805	2.476

- A. Compressed air inlet
- C. Condensation discharge (steam models)
- E. Electrical connection
- F. Fumes extraction
- G. Gas inlet
- V. Steam inlet

	H	I	T	S	A	C	E	F	G	V	W
<b>SPE1000-2600</b>	2.247	1.196	1.208	345	Ø12	1"	5G4	Ø160	1"	1-1/4"	800
<b>SPE1000-3300</b>	2.247	1.896	1.208	345	Ø12	1"	5G4	Ø160	1"	1-1/4"	800