

### ELECTRONIC PROGRAMMER

Simple and easy to use with an automatic mode: automatic management of ironing speed according to the selected temperature.  
Digital display with speed and temperature.

### EFFICIENCY

Good heat conduction thanks to the roll material and thickness: greater control of energy expenditure.  
Automatic shutdown at 80°C (adjustable parameter).  
Fumes circulation circuit from the bottom reducing energy consumption.  
**Radiant gas burners:** +25% more productive

### ROBUSTNESS

Roll driving by speed inverter: smooth operation preventing the wear of belts and mechanical elements.  
Nomex quality feeding and ironing belts: high temperatures resistant.  
Skinplate and stainless steel panels: long lasting.  
Nickel plate cylinder: anti corrosive, more durable (not available in model 200mm).

### ERGONOMICS

Acoustic comfort: <65 dB  
Appropriate operating height: 990mm feeding belts.  
Minimal encumbrance: space saving, suitable for most spaces.  
Electronic control with Auto mode: easy to use, optimized ironing speed.

### MAINTENANCE

Easy access to all components on both sides of the machine.  
Basic connections: electrical connection and air extraction.

### OTHERS

Dries and irons flat linen from a high spin washer extractor in a single operation.  
Front feeding and return.  
Built-in cool down system.  
Polished steel roll Ø 325mm.  
Roll length: 2.000mm, 2.600mm and 3.300mm.  
Heating: electric, gas (atmospheric or radiant burner).  
CE standard






### OPTIONS


- EFFICIENT IRON: Humidity control Ø 325
- Nickel plated roll CM-3332
- Gas LPG option (Propan)
- Gas NG option (Natural Gas)
- 230V I N 50Hz gas CM-3332 ECO-ENERGY
- 230V I N 60Hz gas CM-3332 ECO-ENERGY
- 230V III 50/60Hz electric CM-3332 ECO-ENERGY
- 440V III 50/60Hz electric CM-3332 ECO-ENERGY (maritime)

GENERAL DETAILS	UNIT.	CM-3332 ECO-ENERGY M	
Theoretical production*	Kg/h	85	
	Lb/h	187	
Radiant gas theorial production*	Kg/h	100	
	Lb/h	220	
Evaporation power	l/h	45	
	USgallon/h	11,9	
Roll Ø	mm	325	
	inch	12,80	
Working width	mm	3.300	
	inch	129,9	
Height floor-feeding belts	mm	990	
	inch	39	
Working speed	mt/min	1,5 - 12	
	ft/min	4,9 - 39	
Electronic control	-	YES	
No. Programs (BM Modes)	Nº	2	
POWER			
Heating power	kW	54	
Total electric power	kW	54,52	
Gas heating	kW	69	
Total electric power (gas mod.)	kW	0,52	
Roll motor	kW	0,37	
Fan motor	kW	0,12 x 2	
CONNECTIONS		E	G
Tension 230V I + N + T	nº x mm²/A	-	3 x 2,5 / 6A
	nº x AWG/A	-	3 x 13 / 6A
Tension 230V III + T	nº x mm²/A	4 x 35 / 150A	4 x 2,5 / 6A
	nº x AWG/A	4 x 2 / 100A	3 x 13 / 6A
Tension 400V III + N + T	nº x mm²/A	5 x 25 / 100A	5 x 2,5 / 6A
	nº x AWG/A	5 x 3 / 100A	5 x 13 / 6A
Ø Gas inlet	BSP	1/2"	
DIMENSIONS / PACKING DIMENSIONS			
Net / gross width	mm	3.852 / 3.980	
	inch	151,7 / 156,7	
Net / gross depth	mm	686 / 770	
	inch	27 / 30,3	
Net / gross height	mm	1.112 / 1.400	
	inch	43,8 / 55,1	
Net / gross weight	Kg	655 / 700	
	Lb	1444 / 1543	
Volume	m³	2,94 / 4,29	
	ft³	103,77 / 151,52	
OTHERS			
No fume outlet	Nº	2	
Ø Extraction	mm	98	
	inch	3,86	
Airflow	m³/h	1.000	
	cfm	589	
Sound level	dB	63	

\* 45% moisture



1. Electrical connection
2. Vapour extraction
3. main switch
4. Emergency stop
5. Crank handle
6. Electrical control



	A	B	C	D	E	F	G	H	I	J
CM-2032 ECO-ENERGY M	2.552	2.446	900	750	2.110	980	1.112	140	746	686
CM-2632 ECO-ENERGY M	3.202	3.096	900	750	2.760	980	1.112	140	746	686
CM-3332 ECO-ENERGY M	3.852	3.746	900	750	3.410	980	1.112	140	746	686