

 **FEATURES****TP-A (Without boiler)**

Vacuum ironing table + iron, with electrically heated board and suction.

Work table dimensions 1.200 x 400 x 250mm.

Adjustable temperature of the board by means of a thermostat.

Built-in single phase suction unit.

Works by means of a pedal.

Electric heated board.

Needs to be connected to an external steam supply.

Voltage: 230V I +N 50Hz.

TPC-A / TPC-A PLUS (With boiler)

Vacuum ironing table + iron with suction and electrically heated board, controlled by a thermostat.

Work table dimensions 1.200 x 400 x 250mm.

Built-in electric steam boiler. Iron included.


Automatic water feeding, automatic pressure control.

Feeding pump and emptying valve.

Works by means of a pedal.

Voltage: 400V III +N / 230V III / 230V I +N 50Hz.

TPC-A PLUS: Adjustable height of board from 750 to 950mm.

**OPTIONS**

- Swinging arm with suction and heated sleeve shape MP-4 A-C

CAPACITY	UNIT.	TPC-08 A
		CON CALDERA
Boiler	-	YES
Boiler capacity	L	4
Board dimensions	mm	1.100 x 380 x 270
Adjustable height of board	-	NO
OPTIONS		
Swinging arm with heated sleeve shape	-	OPT
Steam gun	-	NO
Sliding trolley with balancer and lighting	-	NO
Second steam iron assembly	-	NO
POWER		
Vacuum motor	kW	0,13
Pump motor	kW	-
Iron heater	kW	0,8
Board heater	kW	0,7
Boiler heater	kW	1,45
Sleeve-arm heater (option)	kW	0,09
CONNECTIONS		
Ø Water inlet	BSP	-
Ø Boiler exhaust (with boiler)	BSP	-
Ø Steam inlet	BSP	-
Steam pressure	BAR	2,8
Steam Consumption	kg/h	-
Ø Air inlet	BSP	-
Air pressure	BAR	-
Air Consumption	NI/min	-
DIMENSIONS / PACKING DIMENSIONS		
Net width / Gross width	mm	1.380 / 1.300
Net depth / Gross depth	mm	380 / 540
Net height / Gross height	mm	930 / 1.160
Net weight / Gross weight	kg/h	43 / 57
Volume	m ³	0,49 / 0,81
OTHER		
Voltage 50-60Hz	V/Hz	230V 50
Sound level	dB	70