



TOUCH II

- TOUCH II: Easy-to-use microprocessor, fully programmable with a 7" touchscreen.
- USB port: configure, update, and analyse machines without internet connection.
- On-screen videos: add your logo, video advertisements or instructions for use (useful for self-service).
- Multilingual interface.
- 8 standard dosing signals and 6 extra as an option.



G FACTOR

High G-factor of 500 (11-18 kg), 450 (22-80 kg), and 350 (100-120 C).
Reduces residual moisture



EFFICIENCY

Optimal loading: manual indication of weight.
Intelligent consumption: automatic adjustment of water and soap consumptions (standard).
Water Recovery tanks ready: **ECOTANK** and **ECOTANK XL**.
Low water consumption.



VERSATILITY

Make to order: customisation.
OPL < > COIN (mod. DHS-11 up to DHS-45C).
Electric < > Hot water.
Drain valve < > Pump (DHS-11/14).
Wet Cleaning features.



CONNECTIVITY

IoT - **DOMUSCONNECT** standard.
Remote technical service.
Management for laundries: OPL and COIN.
Remote payment DOMUS LAUNDRY App (mod. DHS-11 up to DHS-45C).



ERGONOMICS

Easy opening/closing system for door lock.
Biggest door diameters:

- Ø 373 (11, 14 kg)
- Ø 460 (18, 22, 28 kg)
- Ø 560 (35, 45, 60, 80 kg)
- Ø 700 (100, 120 kg)



MAINTENANCE

Hinged control panel: easy and ergonomic access.
Technical menu: statistics for technicians.



OTHERS

Grey skinplate outer casing.
Drum and vat in stainless steel AISI 304.
Detergent dispenser with 4 compartments.
Electronic control of imbalance with frequency control.
LOADING AID feature: water and rotation control.
Soft mounted washers, free standing.
CB and WRAS approved product. Option ETL.
REG4 standard certified by KIWA.




OPTIONS


- License IoT - DOMUSCONNECT
- Ready for ECOTANK XL conn. 1" for washers DLS/DHS-60C/80C
- DOSING PUMP KIT DQ-2
- EXTRA DOSING PUMP DB-1
- Double drain kit for DHS-60C/80C
- Normally closed valve DHS-60C/80C
- Double tilt for DHS-60C/80C - Available with weighing system
- Front tilt for DHS-60C/80C - Available with weighing system
- Water inlet hose for DHS-60C/80C (one per water intake)
- Weighing sensor system on feet for DHS-60C/80C/100C/120C - Available with tilt systems
- 6 extra dosing signals card for DHS-60C/80C/100C/120C
- Reversible door: reverse door opening
- Steam kit DHS-60C/80C
- Double heating E + S for DHS-60C/80C
- Stainless steel AISI 304 outer casing for DHS-60C
- 440V 3~ (No N) 50/60 Hz DHS-60C (marine)
- Kit watermark Australia
- 230V 3~ 50/60Hz DHS-60C

DRUM	UNIT.	DHS-60C TOUCH II	
Capacity 1/9	Kg	65	
Capacity 1/10	Kg	59	
Volume	l	590	
Diameter	mm	1.048	
Depth	mm	680	
GENERAL DETAILS			
Washing speed / Spining speed	r.p.m.	38 / 875	
G Factor	-	450	
Maximum force transmitted	KN	18 ±4,2	
Frequency-dynamic force	Hz	12,66	
Noise level	dB	< 70	
Coin laundry version	-	NO	
Double drain	-	OPT.	
Weighing system / Tilting door	-	OPT.	
SLUICE option	-	NO	
DOOR			
Height center door / Height door	mm	1.170/810	
Diameter	mm	560	
POWER			
Motor	kW	15	
Electric heating power	kW	36	
Total electric power (electric model)	kW	39	
Total electric power (hw, steam model)	kW	15	
CONNECTIONS			E HW/S
Tension 110V - I + N + T	Nº x mm ² / A	-	-
Tension 230V - I + N + T	Nº x mm ² / A	-	-
Tension 230V - III + T	Nº x mm ² / A	3x25+T - 100A	3X6+T - 40A
Tension 400V - III + N + T	Nº x mm ² / A	4x16+T - 63A	4x10+T - 50A
Steam inlet (Steam model)	inch	3/4"	
Maximum steam consumtion (Steam model)	Kg/h	21	
Water inlet	inch	1"	
Water main pressuer	Kgs/cm ²	2-4	
Maximum water consumption*	Lit/h	598*	
Air inlet	Kg/cm ²	-	
Drain	mm/inch	3"	
Drainage capacity	Lit/min	200	
DIMENSIONS / PACKING DIMENSIONS			
Net Width/Gross width	mm	1.420 / 1.600	
Net Depth/Gross depth	mm	1.433 / 1.595	
Net Height / Gross height	mm	1.890 / 1.930	
Net weight / Gross weight	kg	1.454 / 1.544	
Volume	m ³	4,9	

* Program No. 20: DHS-11 to DHS-45C with 75% load and program no. 2: DHS-60C and DHS-80C with 100% load



1. Soap dispenser
2. Emergency stop
3. USB port
4. Drain 1
5. Drain 2
6. Electric connection to liquid soap pumps
7. Electrical connection
8. Main switch
9. Auxiliar water inlet
10. Hot water inlet
11. Equipotential connection
12. Cold water inlet
13. Steam output
14. Liquid soap connection
15. Steam connection
16. Air intake
17. Ethernet port



	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	CGY	CGZ	
DHS-60C	mm	1420	1433	1890	810	560	760	1050	1563	323	1475	1710	1817	508	912	367	595	720	845	1040	1267	160	1353	608	1500	348	830	820
DHS-80C	mm	1420	1645	1890	810	560	972	1050	1563	323	1475	1710	1817	508	912	367	595	720	845	1040	1267	160	1353	608	1500	348	830	925
	TA	TB	TC	TD	TE	TF	TG	TH	TI	TJ	TK	TL	TM	TN	TO													
DHS-60C	mm	1145	1157	226	799	190	110	265	722	215	300	565	2095	2266	410	422												
DHS-80C	mm	1145	1157	226	1011	190	110	475	510	215	300	602	2137	2478	410	422												