

FEATURES

- Dries, irons and folds linen lengthwise.
 - Folding type: longitudinal.
 - Can be equipped with an automatic feeder (optional), allowing a single operator to manage the feeding of items.
 - Maximum output up to 290 kg/h.*
 - Adjustable ironing speed up to 18 m/min.*
 - Maximum temperature: 165°C.
 - Automatic ironing speed control.
 - Automatic cooling of the ironing roller.
 - Available in one or two work lanes.
 - Intuitive and programmable 7" touchscreen.
 - Fume extraction system with automatic fan cleaning.
 - Customisable with different accessories.
- Key options:

SALIDA POSTERIOR / Rear exit



Recogedor post. + bypass (2/4 vías)
Rear collector + bypass (2/4 lanes)



SMARTY
Plegadora prend. pequeñas
Small garment folder



OPTIONS

- Vacuum belts to help linen feeding
- Automatic 1 lane clamp feeder (needs option of vacuum feeding belts)
- Crossfolder CPL-CROSS 260 with stacker
- Crossfolder CPL-CROSS 330 with stacker
- Rear output with motorised table (H=870 mm. Bypass option required)
- Small pieces back collector: 2 lanes for SP (it needs rear exit + bypass option)
- Small pieces back collector: 4 lanes for SP (it needs rear exit + bypass option)
- By pass for rear exit
- Double air pressure for thick linen
- Linen rejection system (dirty or torn)
- Different voltage from 400V 3~ +N 50 Hz
- Maritime packing for SP

| GENERAL DATA | UNIT. | SP1000-2600 |
|---|-------|---------------|
| Theoretical production elec/steam | Kg/h | 190-230 |
| Theoretical production gas heating* | Kg/h | - |
| Theoretical production radiant gas burner (+20%)* | Kg/h | 228-276 |
| Ø Roll | mm | 1.000 |
| Working width | mm | 2.600 |
| Height floor-feeding | mm | 1.050 |
| Working speed | m/min | 4-18 |
| Control type | - | Digital |
| No. of programs | Nº. | 20 |
| MAIN FUNCTIONS | | |
| Drying | - | YES |
| Ironing | - | YES |
| Longitudinal folding | - | YES |
| Cross folding | - | NO |
| Lateral stacking (Roll-Off or compact stacker) | - | NO |
| FOLDING | | |
| 1 lane - lengthfold | Nº. | 1-2 |
| 1 lane - crossfold | Nº | NO |
| 2 lanes - lengthfold | Nº | 1-2 |
| 2 lanes - crossfold | Nº | NO |
| 4 lanes - lengthfold | Nº | NO |
| 4+ lanes - folding | Nº | NO |
| POWER | | |
| Electric model - Consumption | A | 130 |
| Electric model - Heating power | kW | 90 |
| Electric model - Total electrical power | kW | 92,6 |
| Steam model - Consumption | Kg/h | 200 |
| Steam model - Power (max 12 bar) | kW | 120 |
| Steam model - Total electrical power | kW | 2,6 |
| Liquefied gas (LPG) model - Consumption | m³/h | 4,50 |
| Liquefied gas (LPG) model - Power | kW | 121,30 |
| Natural gas (NG) model - Consumption | m³/h | 12,80 |
| Natural gas (NG) model - Power | kW | 120,9 |
| Gas LPG / NG model - Total electrical power | kW | 2,6 |
| CONNECTIONS | | |
| Ø Gas inlet | BSP | 1" |
| Ø Steam inlet (12 bar max.) | BSP | 1-1/4" |
| Ø Condensed (steam models) | BSP | 1" |
| Ø Air inlet | mm | 12 |
| DIMENSIONS | | |
| Net width / gross width | mm | 3.786 / 3.870 |
| Net depth / gross depth | mm | 1.985 / 2.070 |
| Net height / gross height | mm | 2.180 / 2.380 |
| Net weight / gross weight | Kg | 3.350 / 3.800 |
| Volume | m³ | 16,38 / 19,07 |
| OTHERS | | |
| Exhaust outlet | Nº | 2 |
| Exhaust outlet Ø | mm | 160 |
| Air extraction flow rate | m³/h | 2 x 1400 |
| Air consumption (6.5 bar) | NI/h | 9.500 |
| Noise level | dB | <80 |

* 50% residual moisture, 140gr/m² cotton, 100% roller utilization. Gas with atmospheric burner not available on 1000mm models.



Standard:

- ST 1 - Warning light
- ST 2 - Emergency stop
- ST 3 - Lifting eye bolts (crane)
- ST 4 - Exhaust outlet connection

Options:

- OP 2 - Vacuum feed belts
- OP 3 - Feeder: clips
- OP 31 - Feeder: alignment guides
- OP 4 - Linen reject (button, for SPE / SP models)
- OP 6 - Small pieces back collector (2 or 4 lanes)
- NO - Not available in the SP / S range

