

 **FEATURES****MP-AS (without boiler)**


Vacuum and blowing ironing table + iron, electrically heated.

- Working table: 1,200 x 400 x 270 mm
- Blowing system requires external compressed air supply (compressor)
- Air connection: 1/4", pressure: 5 bar
- Plate temperature adjustable by thermostat
- Built-in single-phase vacuum unit
- Foot pedal operation
- Requires external steam supply and return
- Height adjustable from 750 to 950 mm
- Voltage: 230V 1+N 50Hz

MP-AS-C (with boiler)

Vacuum and blowing ironing table + iron, electrically heated.

- Working table: 1,200 x 400 x 270 mm
- Blowing system requires external compressed air supply (compressor)
- Air connection: 1/4", pressure: 5 bar
- Electric boiler with iron included
- Thermostat-controlled
- Automatic water feeding and pressure control
- Feed pump and drain valve
- Foot pedal operation

**OPTIONS**

- Vacuum sleeve arm for MP-A/MPA-C/MP-AS/MP-AS-C/MP-AC PLUS
- Steam gun for MP-A/MPA-C/MP-AS/MP-AS-C/MP-AC PLUS
- Sliding trolley with light for MP-ASV/MP-ASV-C

CAPACITY	UNIT.	MP-AS
		SIN CALDERA
Boiler	-	NO
Boiler capacity	L	-
Board dimensions	mm	1.200 x 400 x 270
Adjustable height of board	-	YES
OPTIONS		
Swinging arm with heated sleeve shape	-	OPT
Steam gun	-	OPT
Sliding trolley with balancer and lighting	-	OPT
Second steam iron assembly	-	NO
POWER		
Vacuum motor	kW	0,45
Pump motor	kW	-
Iron heater	kW	0,83
Board heater	kW	1
Boiler heater	kW	-
Sleeve-arm heater (option)	kW	0,09
CONNECTIONS		
Ø Water inlet	BSP	-
Ø Boiler exhaust (with boiler)	BSP	-
Ø Steam inlet	BSP	1/4"
Steam pressure	BAR	-
Steam Consumption	kg/h	5
Ø Air inlet	BSP	-
Air pressure	BAR	-
Air Consumption	NI/min	-
DIMENSIONS / PACKING DIMENSIONS		
Net width / Gross width	mm	1.500 / 1.520
Net depth / Gross depth	mm	600 / 580
Net height / Gross height	mm	930 / 1.120
Net weight / Gross weight	kg/h	81 / 97
Volume	m ³	0,84 / 0,99
OTHER		
Voltage 50-60Hz	V/Hz	230V 1 50
Sound level	dB	70