

# **Central steam generator**



### SB-2

Electric steam boiler with steam iron.

Die-cast aluminium boiler, capacity 1,8 liters, heater 1 kW. Manually operated water feeding (drinking water required for its functioning).

Automatic pressure control by thermostat with fixed setting. Mobile trolley as option.

Voltage: 230V I +N 50-60Hz.

## SB-5

Stainless steel electric steam boiler with electric steam iron. Boiler capacity 5 liters, heater 1,45 kW.

Water level indicator with warning light for empty boiler. Three safety devices fitted on the boiler: pressure switch, safety valve and safety thermostat.

Manual water feed. Mobile trolley as option. Voltage: 230V I +N 50Hz.

### SB-24

Electric and automatic steam boiler SB-24 to supply steam to models without boiler. Available from 12 to 22 kW. Water feed can be connected directly to the water mains or to a condensate tank. Pressure between 1 and 7 bar. Capacity 24,9 litres.

Voltage: 230/400V III 50-60Hz.

## TCC

Folding ironing table with electrically heated board and built in suction unit.

Without steam iron, without built-in boiler. Board dimensions: 1.380 x 380 x 930 mm.



GENERAL DETAILS	UNIT.	TCC
	OM1.	TCC
Boiler capacity	L Dor	-
Steam pressure	Bar	
Working temperature	ōC	-
Working humidity	-	-
Boiler Heater	kW	-
Iron Heater	kW	-
Resistance table	W	600
Suction motor	W	100
POWER		
Boiler heaters	kW	-
Steam production	Kg/h	-
Pump motor power	HP	-
CONNECTIONS		
Water feeding inlet	in	-
Boiler exhaust	in	-
Steam inlet	in	-
Condensate return with valve	in	-
Autonomy	-	-
Operating pressure	BAR	-
DIMENSIONS		
Dimensions*	mm	1.380 x 380 x 930
Height with wheel stand mounted (option)	mm	-
Net weight	Kg	22
Gross weight	Kg	32
Packing dimensions	mm	1.460 x 460 x 380
Working dimensions	-	1.100 x 380 x 240
Voltage	V/Hz	230V I 50
Sound level	dB	-

<sup>\*</sup> Dimensions une fois assemblé



